

Charger & Communication Hub for xCL_AT-170

XC-70

A charging with wireless connection to peripheral devices for the xCL_AT-170.

#hypermarket #grocerystore #chainstore #foodcourt #restaurant











SPECIFICATIONS

CPU

- Cortex M4

Operating System

- Embedded Linux

Memory

- 32MB Flash
- 128 MB RAM

Charger Contact

- Charging contact for xCL_AT-170

Wireless Communication

- WIFI 802.11 b/g/n
- Soft Access Mode & Client Mode

Configurations

- 1. Stand Only
- 2. Charger Stand
- 3. Charger Stand + Ethernet + USB host x 2 + RS232 x 2
- 4. Charger Stand + Ethernet + USB host x 1 + RS232 x 2
 - + Modem

LED

- Dual colors LED for different device status

Dimension

- 209.3 (L) x 117 (W) x 54.2 (H) mm

Power Requirement

- 12V/2A DC switching power supply

Environmental

- Operating temperature: 0°C to 50°C
- Storage temperature: -20°C to 60°C
- Operating humidity: 5% to 95% (non-condensing)

Accessory

- Charger stand: 12V/2A Adapter & USB cable (type C to A)
- Charger with IO ports: Power adapter 12V/2A
- Quick user guide/safety instruction

XAC owns the intellectual property of product, and keeps the right to modify the specification herein.