

Charger & Communication Hub for xCL_AT-150E XC-60-CF/EF

- **XC-60-CF:** Charging cradle to support xCL_AT-150E for desktop use.
- **XC-60-EF:** Charging cradle with extensional ports with multiple connection types.



#hypermarket #grocerystore #chainstore
#foodcourt #restaurant

SPECIFICATIONS



CPU

- Cortex M4

Operating System

- Embedded Linux

Memory

- Flash 32MB
- RAM 128MB

Charger Contact

- Pogo connector

Wireless Communication

- XC-60-EF: WIFI 802.11 b/g/n
- XC-60-EF: Soft Access Mode & Client Mode

Configurations

1. XC-60-CF: Charger only
2. XC-60-EF: Charger + RJ-45 Ethernet + USB-A host x 2 + RJ-12 COM x 2

Status LED

- Dual color LED x1

Dimension

- 167.7 (L) x 91.1 (W) x 58.5 (H) mm

Power Requirement

- XC-60-CF: 9V/3A
- XC-60-EF: 12V/4A

Environmental

- Operating temperature: 0°C to 50°C
- Storage temperature: - 20°C to 60°C
- Operating humidity: 5% to 95% (non-condensing)

Accessory

- Power Adapter with cord
- Quick user guide/safety instruction