



XAC Automation Corporation

5.7" Kiosk



**High Security*

**Easy Access*

**Interactive*

本資料為同亨科技股份有限公司專有之智慧財產，非經本公司書面授權，不得透露或使用本資料，亦不得複印、複製或轉變成其他任何形式使用

The above information is the exclusive intellectual property of XAC Automation Corporation and shall not be disclosed, distributed or reproduced without permission of XAC Automation Corporation.



XAC Automation Corporation

5.7" Kiosk

M/B & CPU

IPC Motherboard with Pentium 233 CPU or higher (configuration upgradeable)

Display Touch Screen

5.7" LCD
Capacitive Type Touch Screen

PIN Pad

External Security Module Metal PIN Pad

Reader

Hybrid Insertion Type Reader (EMV Certified)

Printer

80 mm Thermal Printer with Cutter and Presenter

Security

Key Management: Master/Session and DUKPT
Security Algorithms: DES and Triple DES

Power

Input: 110/220V AC $\pm 10\%$ Output: 5/12/24V DC

Dimension

350 mm x 330 mm x 440 mm

Environmental

Operating Temperature: 0°C to 50°C
Storage Temperature: -40°C to 70°C
Relative Humidity: 5% to 95 % Non-Condensing

XAC AUTOMATION CORP.

**Address: 4F, No. 30, Industry E. Road IX,
Science-Based Industrial Park
Hsin-Chu, Taiwan, ROC**

Phone: +886-3-577-2738

Fax: +886-3-567-8022

E-mail: marketing@xac.com.tw