

xCL_RS-1.0 Mobile SCRP

- PCI PTS/SCRP 7.x
- Certified EMV Contact & Contactless readers
- With rechargeable battery
- Bluetooth communication
- Compact and portable
- Optional charging cradle



#gaspump #parkingmeter #vendingmachine
#billpaymentkiosk #hospital



SPECIFICATIONS

CPU

- ARM Cortex M3 secure processor

Operating System

- RTOS

Contactless Reader Standards

- ISO 14443 type A/B
- NFC: ISO 18092
- Mifare
- Sony Felica
- EMV Contactless Level 1
- Paywave, Paypass, DPAS
- Optional:
ExpressPay, JCB Speedy, CUP
Quickpass, Interac Flash

Contact Reader Standards

- EMV Contact L1 approval (T=0 & T=1 type)
- EMV Contact Level 2
- SLE4442 Memory Card

Communication Interface

- USB 2.0 (TypeC) x1
- Bluetooth BLE

Features

- Large contactless landing zone identifier
- 4 LED sequence indicators
- Audible buzzer
- Device firmware programmable with upgrade capability
- Designed for front mounting and rear mounting directions
- Encryption: AES, TDES, RSA, ECC

Certification

- PCI PTS/SCRP 7.x

Regulatory Certificates

- CE
- FCC

Battery

- 3.8V/680 mAh

Dimension

- 69mm(W)x69mm(H)x16.5mm(D)

Power Requirement

- 5V/1A

Environmental

- Operating Temperature :
-0°C to 50°C
- Storage Temperature :
-20°C to 60°C
- Operating Humidity :
5% to 95% RH (non-condensing)

Accessory

- USB cable (type C to A)
- Optional Power adaptor (5V/1A)