

# 5" Handheld Payment Terminal

## xCL\_AT-150R

*xCL\_AT-150R Mobile Payment Terminal leverages secured Android platform and XAC PCI PTS 5.x secure payment modules in a compact design to process magnetic card swiping, EMV, PIN entry, and NFC/contactless transactions, connecting with Wi-Fi and 4G in anywhere there is wireless coverage.*



**#retail #restaurant #hypermarket #grocerystore  
#chainstore #foodcourt**



## SPECIFICATIONS

### CPU

- ARM Cortex-A7 microprocessor cores (quad-core) up to 1.1GHz

### Operating System

- Android 8.x

### Memory

- 1GB DDR3 SDRAM
- 8GB eMMC Memory

### Display

- 5" 1280x720 color TFT
- Capacitive touch screen display

### AUDIO

- Audio Jack and Microphone

### PINPAD

- Touch PINPAD

### Magnetic Stripe Reader

- ISO 7811 compliant 3-track MSR

### Smart Card Reader

- ISO7816-1/2/3 compliant Asynchronous Card protocol T=0, T=1, and SLE4442 Memory Card
- Up to 2 SAM, Support 3V SAM card

### Contactless Reader

- ISO14443 type A/B, MiFare
- PayPass, PayWave, DPAS, ExpressPay, Quickpass
- NFC (ISO18092)

### Security

- Algorithm: 3DES, AES, RSA
- Key Management: MK/SK, DUKPT
- TLS 1.2 support
- Secure Code Update Architecture

### Certification

- PCI PTS 5.x with SRED
- GBIC, and CC compliant
- EMV Contact L1 & L2
- EMV Contactless L1
- Mastercard TQM (IFM/PCD)
- PayPass, PayWave, DPAS, ExpressPay, Quickpass compliant

### Thermal Printer

- 48 mm printing width with tear bar

### Communication

- Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz)
- Bluetooth 4.2 dual mode
- 4G wireless, SIM x2 (optional)

### Extension Ports

- USB Type C Connector x 1

### Barcode Reader (Optional)

- Support 1D/2D barcode scanning

### GPS (Optional)

- GPS Tracking

### Power for xCL\_AT-150-R3

- USB Charge: 5V/2A
- Li-Ion Battery (3000mAh)

### Power for xCL\_AT-150-R6

- USB Charge: 5V/3A
- Li-Ion Battery (6700mAh)

### Dimension

- 181(L) x 82.6 (W) x 64.9(H) mm

### Environmental

- Operating Temperature: 0°C to 50°C
- Battery Charging Operating Temp.: 0°C to 45°C
- Storage Temperature: - 20°C to 60°C
- Operating Humidity: 5% to 85% (non-condensing)

### Accessory

- DC switching power adapter with cord
- USB cable (type C to type A)
- Rechargeable battery
- Paper roll
- Quick user guide/safety instruction