

# Charger & Communication Hub for xCL\_AT-170

**XC-70** 

A charging with wireless connection to peripheral devices for the xCL\_AT-170.

#hypermarket #grocerystore #chainstore #foodcourt #restaurant











# **SPECIFICATIONS**

## **CPU**

- Cortex M4

# **Operating System**

- Embedded Linux

### **Memory**

- 32MB Flash
- 128 MB RAM

## **Charger Contact**

- Charging contact for xCL\_AT-170

## **Wireless Communication**

- WIFI 802.11 b/g/n
- Soft Access Mode & Bridge Mode

# **Configurations**

- 1. Stand Only
- 2. Charger Stand
- 3. Charger Stand + Ethernet + USB host x 2 + RS232 x 2
- Charger Stand + Ethernet + USB host x 1 + RS232 x 2 + Modem

#### **LED**

- Dual colors LED for different device status

## **Dimension**

- 209.3 (L) x 117 (W) x 54.2 (H) mm

## **Power Requirement**

- 12V/2A DC switching power supply

### **Environmental**

- Operating temperature: 0°C to 50°C
- Storage temperature: -20°C to 60°C
- Operating humidity: 5% to 95% (non-condensing)

### **Accessory**

- Charger stand: 12V/2A Adapter & USB cable (type C to A)
- Charger with IO ports: Power adapter 12V/2A
- Quick user guide/safety instruction

## XAC owns the intellectual property of product, and keeps the right to modify the specification herein.