

xCL_AT-150-U Smart UPT

- **Built in 4G antenna* to save extra cost & effort**
- **5MP camera* for best decoding performance**
- **Auto-adjustable light sensor* for better visual experience**
- **Rugged design with UV and water resistant**
- **Enable fingerprint* authentication**
- **Able to drive 2nd display**
- **MDB slave supported**



#kiosk #hospitality #ticketing #vendingmachine
#parkingmeter #drivethrough #bank



SPECIFICATIONS

CPU

- Qualcomm ARM Cortex-A53 quad-core 64bit (QCM2290) up to 2.0GHz
- Secure: MAXIM ARM Cortex-M3 SoC

Operating System

- Android 12

Memory

- 2 GB SDRAM +16 GB eMMC
- Optional up to 4 GB SDRAM +64 GB eMMC

Display

- 5" 1280x720 pixel TFT color display
- Capacitive Touch (PIN Entry)
- Auto adjustable brightness (Optional)

Magnetic Stripe Reader

- ISO 78113 tracks MSR

Smart Card Reader

- EMV L1 approval (T=0 & T=1 type)
- Landing type card slot with light guide
- Support up to 4 SAM slots (Optional)

Contactless Reader

- ISO14443 type A/B
- NFC (ISO18092)
- Mifare
- SONY FeliCa

Barcode Reader (Optional)

- 5MP auto focus front facing camera
- 5MP fix focus bottom camera with aiming and flash LED

Connectivity

- Power jack x1
- USB-C x1
- RS232 x1
- Optional Extension Hub
 - USB 2.0-A x2
 - Ethernet 10/100 RJ-45 x1
 - MDB Slave x1

Wireless Communication

- Wifi 802.11 a/b/g/n/ac (2.4G & 5G)
- Bluetooth BLE
- 4G LTE with built-in antenna (Optional)

Security

- Algorithm: 3DES, RSA
- Key Management: MK/SK, DUKPT
- Mutual Authentication
- Message Encryption
- PCI compliant Load Key process

Certification

- PCI PTS 6.x with SRED
- GBIC, and CC compliant
- EMV Contact L1 & L2
- EMV Contactless L1
- Mastercard TQM (PCD/IFM)
- PayPass | PayWave | DPAS | ExpressPay | China UnionPay | JCB J-Speedy
- Google Pay | Apple Pay | Samsung Pay | Apple Pay VAS | ECP2 | Google Smart Tap

Audio

- Mono Speaker
- Audio Jack (Optional)

Secure Fingerprint Module (AT150U-FP)

- FBI PIV certified
- Sensing area: 12.8mm x 18mm

Safety & Environmental Compliance

- FCC | CE | CB | UL
- ROHS/WEEE/REACH
- IP65 | IK08
- High durability UV proof rated plastic

Power source

- 12V~45V input

Dimensions

- AT150-U: 166 (L) x 93(W) x 55(D) mm
- AT150-U-FP: 201(L) x 93(W) x 55(D) mm

Environmental

- Operating Temperature: -20°C to 70°C (without heater option)
- Operating Temperature: -40°C to 70°C (with heater option)
- Storage Temperature: - 40°C to 80°C
- Operating Humidity: 5% to 95% (non-condensing)

Accessory

- 12V/2A Power adapter & cord (indoor use)
- Installation bezel
- Quick user guide/safety instruction
- USB display dongle (Option for Android12)
 - Drive 2nd touch display to support
- ECR POS/KISOK/Vending Machine Customer Facing Touch Display