

WEB BASED CLOUD TERMINAL

T401se



XAC's T401SE 5.6" Web Based Terminal can be configured with stand-alone thermal printers, cash drawers, programmable keyboards, barcode scanners, PIN pads, and card readers to provide cost-effective alternatives to POS systems.

**#vendingmachine, #shoppingmall,
#departmentstore, #hypermarket, #bank,
#moneytransfer, #cafeteria, #unattendedservice,
#ticketing, #kiosk**



SPECIFICATIONS

CPU

- 32-bit RISC ARM 9 processor

Operating System

- WinCE 6.0 Core (SDK for C++ and .NET available)

Memory

- 1GB Flash and 128MB SDRAM

Display

- 5.6" VGA (640x480) resolution
- 4-wire resistive touch screen

Magnetic Stripe Reader

- ISO 7811 compliant 3-track MSR (supports over 1M swipes)

Interface Ports

- Ethernet x 1
- Modem x 1
- RS232 x 3
- USB Host x 4
- USB device x 1
- Wireless (3G/WCDMA) (USB optional)
- WI-FI (USB optional)

Security

- Secure Program and Parameter Loading (PPL)
- TLS 1.2
- Voltage SecureData Payment SDK

Dimension

- 180(W) x 140(H) x 42 (D) mm

Power

- 12V~24V DC Input 7W (no 3G)
- 12V~24V DC Input 12W (with 3G)

Environmental

- Operating Temperature: 0°C to 50°C
- Storage Temperature: - 20°C to 70°C
- Operating Humidity: 5% to 95% (non-condensing)

Mounting

- VESA compliant

Accessory

- 12V Power Adapter/cord

Options

- RS232-DB9 Cable
- Desktop Stand
- 3G module
- Wi-Fi module
- 48mm printer base unit