

Charger & Communication Hub for xCL_AT-150-ATEX XC-55

A charging with wireless connection to peripheral devices for the xCL_AT-150-ATEX.



SPECIFICATIONS

CPU

- Cortex M4

Operating System

- Embedded Linux

Memory

- 32MB Flash
- 128 MB RAM

Charger Contact

- Charging pads for xCL_AT-150ATEX & xCL_E200NP
- Mounting design support (Option)

Wireless Communication

- WIFI 802.11 b/g/n
- Soft Access Mode & Client Mode

Configurations

- 1. Stand Only
- 2. Charger Stand
- 3. Charger Stand + Ethernet + USB host x 2 + RS232 x 2
- 4. Charger Stand + Ethernet + USB host x 2 + RS232 + Modem





LED

- Dual colors LED for different device status

Dimension

- 171 (L) x 91 (W) x 51.4 (H) mm

Power Requirement

- 12V/2A DC switching power supply

Environmental

- Operating temperature: 0°C to 50°C
- Storage temperature: 20°C to 60°C
- Operating humidity: 5% to 95% (non-condensing)

Accessory

- 12V / 2A Power Adapter and cord
- Quick user guide/safety instruction

XAC owns the intellectual property of product, and keeps the right to modify the specification herein.

Founded in 1993, XAC (TAIWAN OTC Securities Exchange 5490) is a leading R&D/Manufacturing company focused on transaction automation devices. XAC develops key component modules and low-cost secure platform architectures that can be leveraged to design customized solutions for its customers/partners. Today, XAC's technology can be found in cost-effective POS terminals, high-end countertop payment devices, Electronic Cash Registers (ECRs), wireless "pay-at-the-table" devices, multi-lane consumer activated terminals, outdoor payment terminals, PIN pads, Smartcard peripherals, RFID readers, gaming machines, cashless ATMs, kiosks, and counters olutions. With a flexible and efficient manufacturing infrastructure, "in-house" key components, modules, and technical design expertise, XAC delivers cost-effective, high-quality solutions to customers in a timely manner. For more information about XAC, please visit <u>http://www.xac.com.tw</u>.